Matls. I.M. 483.06

INSPECTION AND ACCEPTANCE OF PAVEMENT MARKING TAPES

GENERAL

Pavement marking tapes shall meet the applicable requirements in <u>Section 2527.02</u> and <u>Section 4183.06</u> of the Iowa Department of Transportation Standard Specifications.

ACCEPTANCE

Acceptance of pavement marking tapes shall be on the basis of brand name approval, and satisfactory field performance.

Pavement marking tapes shall be approved prior to installation on a project. Approval does not preclude the need for acceptance sampling and testing on a project-by-project basis.

Approved brand names are listed in Appendix A.

BRAND NAME APPROVAL

Request for approval shall be made to the Office of Materials in Ames, Iowa. This shall include a complete product description, instructions for application, and the recommended usage. A sample of at least 30 m (90 ft.) of 100 mm (4 in.) wide tape of each color shall be furnished.

In addition, the tapes shall be submitted to a National Transportation Product Evaluation Program (NTPEP) test deck.

Tapes shall be evaluated for four months during non-snow plowing weather. The tapes shall adhere to the pavement surface without excess movement. The color shall stay in the chromaticity box for standard highway colors. The retro reflectivity in the wheel path area shall stay above 150 for white and 100 for yellow when measured by a retroflectometer with 30 meter geometry.

Approval of marking tapes may be withdrawn because of deficient test results on samples; product changes made after the original qualification, or unsatisfactory field performance. Samples of the marking tape on which a qualification was based will be used as the standards for comparison with tapes supplied to projects.

MONITOR SAMPLING AND TESTING

The Office of Materials may sample and test marking tapes to verify compliance with specifications. Such samples will be a continuous 3 m (10 ft.) section.